




•

貴社No.F008769 幣所No.EP9002


F I G. 3











,











COPERATION CONDITION	ر م								
OPERATION CONDITION MAIN MEMORY SIDE: ST DA	ARTI TA I	ng, S AN	addre Eve	ه کک م سر	F RI	200 Z	ENG1	Ή	貴社No F008769
LOCAL MEMORY SIDE: S NUMBER OF BYTES IN 1	TA127	iing	ADI	DRESS	or	IMA	GE	DATA	幣所以O EP9002
NUMBER OF RYTES -	٦٨	€V€	ر ا	E					FIG. 9
7/13/20 1/	INE	· 16	(45) B>7	₹ \$					
動作条件	というげ	z =	<i>।</i> ବେ ଶ ଞ୍ଜ	# 2/ 51	, z/æ	数すら	.7		
動作条件 メインメモリ側:ランローカルメモリ側:イン ローカルメモリ側:イン 1ラインバイト数:16	1-157 141-	739	開始	كما	温数	7502			
mangy Mangy				DI	ECU				
1 1/2 01 \$41231-1-1-01		To 1			····	 -		 	
03 02 FACE A - A面	01 01	01	 		 -				·
44 FB 17 32 → 03 02		 	<u>. </u>	<u> </u>	L	<u> </u>	L	1	
FF FE TRANSFER ST ATT	01 01	01 02							
		<u> </u>	<u> </u>	<u> </u>	<u> </u>				
66 12 新送63 → 78 55 77 45 FACE A → 本面		01 02	170 55	1		·		<u>, </u>	
89 10 下4年 B 一日面	01 01	01 02	76 33						
55 CO 42-404 A4 CO		<u> </u>	<u> </u>	<u> </u>				<u> </u>	
10 FA FACE A FACE		01 02	78 55	44					
20 08 FACE B 一日面									
12 13 転送85 → FF FE									TRANSFER D1
14 15 TRANSFEL SS A面 FACE A	01 01	01 02	78 55	44 FF	FF FF	FF FF	FF		
16 17 FACE 13 一日面			L						
18 19 ★ 36 → 11 06	01.01	[n1 n2	70 55	144 55	<u> </u>	CE		111 11	
14 201 1466 7	01 01	01 02	/8 33	44 FF	rrrr	7777	FF []		─ ───>
98 BO #=: ¥07 - 66 12		<u> </u>	<u> </u>						
EZ EC TRANSFOR ST AND	-								
warmaning talk w	66 12								
FF FE 就送33 → 77 45									
FC FD TRANSFER ST AND									
FE FF FAIF IS — B面	66 12	77 45							
Transfer sq - 粒送3 9→89 10		_							
	66 12	77 45	90 10						
TRANSFER SIO - \$55 FB	00 12	17 40	03 10	1					
FREE A ATE								<u> </u>	
から 一多面	66 12	77 45	89 10	55					
TRANSFER SH _ 10 FA									TRANSFER DZ
FACE A									
TRANSFER FACE B 一日面	66 12	77 45	89 10	55 10	10 10	10 10	10		
TRANSFER 512 - 表送S12 20 08									₹送02
•		20 20							
FACE B ——B面	66 12	77 45	89 10	55 10	10 10	10 10	10 20	20 20	

FIG. 10

DECU

TRANSTER 513 20 20 20 20 12 13 FACE B TRANSFER 574 ---14 15 20 20 20 20 12 13 14 15 FACEA 一人面 - 8面 FACEB TRANSFER STS ___ 16 17 20 20 20 20 12 13 14 15 16 17 日面 FACEB TRANSFER S16 - 報送316 20 20 20 20 12 13 14 15 16 17 18 19 FACEB — 日面 TRANSTER S17 - 最近817 20 FD TRANSFER D3 FACEA 20 20 20 20 12 13 14 15 16 17 18 19 20 FACEB TRANSFER SIE ____________ 20 20 20 20 12 13 14 15 16 17 18 19 20 11 11 11 FACE 8 -BE TRANSFER SIA -98 80 FACE B —— 日面 11 98 B0 TRANSFER SZO - FZ FC FACEA 一人在面 ficeB — B面 11 98 B0 F2 TRANSFER 521 ____ 本送S21 - AB 03 FACEA 一本面 faces 一日面 11 98 B0 F2 AB AB AB AB AB TRANSFER S22 - FF FE FACEA ——人面 FACE D ---B面 11 98 BO F2 ABABABABAB FFFE TRAMSFER SZ3 - 転送SZ3-FC FD TRANSFER D4 FACEA facir B — B面 11 98 BO F2 ABABABABAB FF FE FOFD TRANSFER 524 - 転送824- FE FF FACT A ___A FACE 8 __ 各面 11 98 BO F2 ABABABABAB FF FE FOFD FF FF FF

SETTING CONDITION

NO VERTICAL LINE REARRANGEMENT

TOTAL NUMBER OF DEVELOPED BYTES: 64 BYTES (1(X4))

NUMBER OF BYTES IN 1 LINE: 16 BYTES

NUMBER OF DEVELOPED LINES: 4 LINES

FIG. 11

貴社No. F008769 幣所No. EP9002

)設定条件 ライン縦並び変換なし 総展開バイト数:64パイト(16×4) 1ラインバイト数:16パイト 展開ライン数:4ライン

DESTITUTED LOCAL MEMORY

(a)

O1 01 01 02 78 55 44 FF

FF FF FF FF FF 11 11 11 11

66 12 77 45 89 10 55 10

10 10 10 10 10 20 20 20

20 20 20 20 12 13 14 15

16 17 18 19 20 11 11 11

D4 11 98 B0 F2 ABABABABAB

AB FF FE FC FD FF FF FF

